

VT42AEMM Mirror Monitor Rear Vision System Technical Specification

Overview

All the benefits of the space-saving system with added versatility where the ultra-compact monitor is replaced by a clever mirror monitor which acts as a useful deterrent to opportunist thieves who may think the ordinary camera monitor is a Satellite navigation system.

Complete system comprises of 4.2" mirror monitor, compact colour camera, cable and fixings.

The 4.2 " mirror monitor and suspended camera is suitable for any commercial vehicle application. The monitor can be used with the **VT56AE** camera if a more rugged camera is required.

Key Specifications

Monitor

- 4.2" LCD profile wide screen ratio 16:9
- View angle (U/D/L/R):25/45/45/45
- Resolution: 320(V)*234(H) TV lines
- Power Requirements : 12-24 DC
- Operating Temp. Range: -20°C to +70°C (±3)
- Dimensions 280(L) x 91(W) x 30 (D)

Camera

- Image Type: Colour SONY CCD
- Resolution (pixels):PAL:500(H)*582(V)
,NTSC:510(H)*492(V)
- Image Size: 1/4 Inch
- Lens: 2.1mm, F2.0
- Lens angle130°/150°
- Horizontal Resolution:420TVL
- IP 67 waterproof, & dust resistance
- Power Supply: DC12V±10%
- Power Consumption: ≤1W
- Operating Temperature Range: -30° to +65°

Certifications

- E-mark
- RoHS
- FCC
- IP67 Waterproof & dust resistance Test
- Salt-Spray Test Approval



For further information...